

LG200: Forward and reversible plate for soil and gravel applications

3382 0000 66



[Opprett PDF-ark](#)

[Be om informasjon](#)

Kontakt

[Vis kontaktinformasjon](#)

Hurtigkoblinger

[Atlas Copco Print Shop](#)

[Atlas Copco Multimedia Gallery](#)

Produktinformasjon

High speed and world-class compaction efficiency make our forward and reversible plates excellent for compacting medium to deep layers of granular soils. The high speed, balanced design and hydraulic control system contributes to easy, precise handling on the roughest of surfaces or for spot compaction.

Features & benefits

Hydraulic forward/reverse lever

Engines with low fuel consumption and emissions

Heavy-duty protection frame and impact resistant steel covers protect engine and transmission.

High quality bottom plate

Applications

Cobbles and boulders

Sand and Gravel

Silt

Technical data

Enheter: **Metrisk** [Britisk måleenhet](#)

Tekniske spesifikasjoner	
Driftsvekt	231 kg
Sentrifugalkraft	36 kN
Platebredde	500 mm
Motormerke	Hatz
Effekt	3.1 kW
Turtall	25 m/min
Utslagsvidde	1.9 mm
Frekvens	65 Hz
Lydeffektnivå, garantert	108 dB(A)
Lydtrykknivå ved operatørens øre	90 dB(A)
Verdi for vibrasjonsbelastning	3.5 m/s ²